



ArtNo.

LB5315

Technical Data

| | |
|---------------------|-------------------|
| RANGE | INDOOR |
| MOUNTING | CEILING RECESSED |
| LUMEN OUTPUT | 4000LM |
| LIGHT INTENSITY | 400MCD |
| LIGHT SOURCE | NICHIA |
| POWER | 50W |
| INPUT | 100-240VAC |
| OPERATING FREQUENCY | 50/60HZ |
| IP RATE | IP20 |
| DIMENSION | 600X600X12 |
| MATERIAL | EXTRUDED ALUMINUM |
| LIFE TIME | 50000HRS |
| WORKING TEMP | -25°C~+50°C |
| WARRANTY PERIOD | 5YEARS |
| WARRANTY TYPE | REPAIR |
| SAFTY CLASS | I |
| NW KGS | 6 |
| GW KGS | 7.5 |
| CBM | 0.01 |
| EFFICACY | 80 |
| CERTIFICATION | CE,SELV,ENEC |

Product Characteristics

| | |
|-----|--------|
| CRI | 80, 90 |
|-----|--------|

| | |
|------------|----------------------------|
| CCT | 2700K, 3000K, 4000K, 6000K |
| Finish | White, Black, Silver |
| Beam Angle | 120 |
