



ArtNo.

LA9408

Technical Data

RANGE	OUTDOOR
MOUNTING	CEILING/WALL/SURFACE/POLE MOUNTED
LUMEN OUTPUT	42,390LM
LIGHT SOURCE	LUMILEDS 5050
POWER	240W
INPUT	180-277VAC
POWER FACTOR	>0.95
OPERATING FREQUENCY	50/60HZ
FUNCTION	ON/OFF
IP RATE	IP66
DIMENSION	344X184X238MM
MATERIAL	ALUMINUM+PC
LIFETIME	50,000HRS
WORKING TEMP	-40°C - + 55°C
WARRANTY PERIOD	5 YEARS
WARRANTY TYPE	REPAIR
SAFETY CLASS	1
NW KGS	5.5KG±5%
GW KGS	6.1KG±5%
IK RATE	IK10
APPLICATION	LARGE STADIUMS, AIRPORTS, PARKING LOTS, TERMINALS, TENNIS COURTS, GOLF COURSES, POWER STATIONS, COMMERCIAL PARKS ETC.
CERTIFICATION	CE,CB,ROHS

Product Characteristics

CRI	70, 80
CCT	2700K, 3000K, 4000K, 5000K, 6000K, 6500K
FINISH	BLACK
BEAM ANGLE	30, 60, 90
