



ArtNo.

LB9558

Technical Data

RANGE	OUTDOOR
MOUNTING	SUSPENDED
LUMEN OUTPUT	30000LM
LIGHT INTENSITY	3000MCD
LIGHT SOURCE	NICHIA
POWER	200W
INPUT	100-277VAC
EFFICIENCY	≥90%
POWER FACTOR	≥0.95
OPERATING FREQUENCY	50/60HZ
FUNCTION	OCCUPANCY, DALI, 1-10V DIMMING, ZIGBEE WIRELESS, DAYLIGHT
IP RATE	IP65
DIMENSION	Ø383X193.5
MATERIAL	ALUMINUM ALLOY
SUSPENDED LENGTH	1500MM
LIFE TIME	50000HRS
WORKING TEMP	-30°C~+50°C
DIFFUSER	TOUGH PROTECTION TEMPERED SAFTY GLASS
WARRANTY PERIOD	3YEARS
WARRANTY TYPE	REPAIR
SAFTY CLASS	I
EEC	A++
APPLICATION	INDUSTRIAL, WAREHOUSES, INDOOR STADIUMS, FACTORIES, WORKSHOPS, AUDITORIUMS
CERTIFICATION	CE,CB,SAA,UL,ROHS,ENEC,GS,SASO,EMC,PSE,DLC

Product Characteristics

We reserve the right for technical and design changes without prior notice or announcement.
For latest product update please refer www.lumibright.co.uk

CRI	70, 80
CCT	5000K
FINISH	BLACK
BEAM ANGLE	50, 60
