



ArtNo.

LB2856

Technical Data

RANGE	INDOOR
MOUNTING	CEILING RECESSED
OUTPUT CURRENT	600MA
LUMEN OUTPUT	1600LM
OUTPUT VOLTAGE	24-42VDC
LIGHT SOURCE	OSRAM LED
POWER	10X2W
INPUT	220-240VAC
POWER FACTOR	>0.90
OPERATING FREQUENCY	50/60HZ
FUNCTION	ON/OFF
IP RATE	IP20
DIMENSION	L279XW45XH52MM
CUT OUT	272X37MM
MATERIAL	DIE-CAST ALUMINIUM+THERMOPLASTIC
LIFE TIME	50,000HRS
WORKING TEMP	-20°C~+40°C
DIFFUSER	CLEAR PC
WARRANTY PERIOD	5 YEARS
WARRANTY TYPE	REPLACE
SAFTY CLASS	II
EFFICACY	80LM/W
APPLICATION	VILLA & APARTMENT, RESTAURANT, COMMERCIAL BUILDINGS, OFFICES, PUBLIC AREAS, RETAIL STORES

We reserve the right for technical and design changes without prior notice or announcement.
 For latest product update please refer www.lumibright.co.uk

CERTIFICATION

CE/ROHS

Product Characteristics

CRI	80, 90
CCT	2700K, 3000K, 4000K, 5000K, 6000K
Finish	White + Black
Beam Angle	15, 30, 45
Drivers	On/Off
