



ArtNo.

LB2149

Technical Data

| | |
|---------------------|-------------------|
| RANGE | INDOOR |
| MOUNTING | SURFACE MOUNTED |
| LUMEN OUTPUT | 995LM |
| LIGHT INTENSITY | 99.5MCD |
| LIGHT SOURCE | BRIDGELUX |
| LAMP TYPE | COB LED |
| LAMP QTY | 1 |
| POWER | 15W |
| INPUT | 220-240VAC |
| BEAM ANGLE | 24 |
| OPERATING FREQUENCY | 50/60HZ |
| IP RATE | IP20 |
| DIMENSION | Ø80X222 |
| MATERIAL | EXTRUDED ALUMINUM |
| LIFE TIME | 50000HRS |
| WORKING TEMP | -25°C~+50°C |
| REFLECTOR | ANODIZED ALUMINUM |
| HEAT SINK | DIE CAST ALUMINUM |
| WARRANTY PERIOD | 5YEARS |
| WARRANTY TYPE | REPAIR |
| SAFTY CLASS | I |
| EEC | A++ |
| NW KGS | 22.8 |
| GW KGS | 23.8 |

We reserve the right for technical and design changes without prior notice or announcement.
 For latest product update please refer www.lumibright.co.uk

| | |
|---------------|--------------|
| WIDTH | 24.5CM |
| HEIGHT | 56CM |
| LENGTH | 38.5CM |
| CBM | 0.2 |
| EFFICACY | 66 |
| CERTIFICATION | CE,SELV,ENEC |

Product Characteristics

| | |
|------------|--|
| CRI | 80, 90 |
| CCT | 2700K, 3000K, 4000K, 6000K, 5600K |
| Finish | Painted in Black, Black With Sand + Black, White + Painted in black, White With Sand + Golden, Black With Sand + Golden, White With Sand + Black With Sand |
| Beam Angle | 24, 32, 50 |
